

PROJECTION EQUIPMENT

Projectors

BARCO HDX W20 FLEX



EPSON EB-2255U



EPSON Laser EB-L1755U



EPSON Laser EB-PU1008B





BARCO HDX W20 Flex

Technical Specifications

| | |
|---|--|
| • Projector type | WUXGA 3-Chip DLP digital projector |
| • Technology | 0.96" DMD x 3 |
| • Resolution | 1,920 x 1,200 |
| • Light output | 20,000 Center lumens / 8,500 ANSI lumens |
| • Contrast ratio | 1,850:1 (standard) – 2,400:1 (high contrast mode) |
| • Brightness uniformity | 90% |
| • Aspect Ratio | 16:10 |
| • ScenergiX | horizontal and vertical edge blending |
| • Lens type | TLD + |
| • Optical lens shift | Vertical: -10% to + 110% / Hori zontal: +/-30% on zoom lenses (memorized) |
| • | |
| • Color correction | P7 |
| • Lamps | 2.5 kW Xenon |
| • Sealed DLP™ core | Standard |
| • Optical dowser | Standard |
| • Picture-in-picture | Two sources simultaneously |
| • Orientation | table – ceiling – side (portrait)* – vertical * lamp door down/bottom |
| • DMX 512 | Standard |
| • WARP | direct adjust OSD + toolset |
| • Integrated web server | Yes |
| • CLO (constant light output) | standard |
| • Inputs | DVI-I (HDCP including analog RGB YUV) / SDI / HDSDI / dual HDSDI / 3G / BarcoLink |
| • AC power | 200-240 V / 50-60 Hz |
| • Power consumption | 2,850 W / STBY<8W |
| • Noise level (typical at 25°C/77°F) | 53 dB (A) |
| • Operating temperature | 0 ~ 40°C / 32 ~ 104°F |
| • Operation humidity no condens | 0% – 80% |
| • Dimensions (WxLxH) | 475 x 725 x 382 mm 18.70" x 28.54" x 14.96") |
| • Weight | 50kg (110lbs) |



EPSON EB - 2255U

Technical Specifications

- **Light Output** 5000 ANSI lumen
- **Resolution** 1920 x 1200 (native)
- **Brightness** 5000 lumens (white light output & colour light output)
- **Contrast ratio** 15000:1 (full field)
- **Full compatibility, Wired and wireless connectivity**
- **Multi-PC projection, Split screen, Remote management and control tools**
- **Lamp** 300W UHE (Ultra High Efficiency)
- **Weight** 4.7 kg (10.4 lbs)



EPSON Laser EB - L1755U

Technical Specifications

| | |
|---|--|
| • Light Output | 15000 ANSI lumen |
| • Resolution | 1920 x 1200 (native) |
| • Brightness | 15000 lumens (white light output & colour light output) |
| • Contrast ratio | 2000:1 (native) 2500000:1 (dynamic) |
| • Interchangeable lens | |
| • Wired and wireless compatibility | |
| • Light Source | Laser |
| • Weight | 24.1 kg (53.1 lbs) |
| • Room Type | Boardroom, Large Meeting Room/Auditorium, Projection Mapping, Rental/ Staging, Signage/Retail, Visitor Attractio |



EPSON Laser EB - PU1008B

Technical Specifications

| | |
|---|--|
| • Light Output | 8500 ANSI lumen |
| • Resolution | 1920 x 1200 (native) |
| • Brightness | 8500 lumens (white light output & colour light output) |
| • Contrast ratio | Over 2500000:1 (dynamic) |
| • Interchangeable lens | |
| • Wired and wireless compatibility | |
| • Light Source | Laser |
| • Weight | 16.3 kg (35.9 lbs) |
| • Room Type | Boardroom, Large Meeting Room/Auditorium, Meeting Room/Classroom, Projection Mapping, Rental/Staging, Signage/Retail, Visitor Attraction |